



2200 & 3200 SERIES COMMON DRIVE CONVEYORS



Driving multiple conveyors from a single gearmotor to maximize energy efficiency and space!

- Conveyors move at same relative belt speed
- Creates single lanes for handling parts
- Wide parts or pallets can be carried by each conveyor to allow access from below
- Conveyors can be of different widths and lengths

Features & Specifications

- Available on Dorner 2200 & 3200 Series Belt End Drive Conveyors
- Aluminum extruded frame with T-Slot construction
- Sealed ball bearings
- V-Guided and Non V-Guided belt compatible
- Rack and pinion belt tensioning
- Reference the conveyor specification sheet or www.dorner.com for additional details and specifications

Common Drive Specifications

- Fixed conveyor locations
- Load capacity: contact factory for details
- Compatible with all standard end drive gearmotor mounting packages
- Includes aluminum extruded conveyor tie bar assembly with belt return roller
- Includes common drive couplings and guarding
- Multiple conveyor spacing options

Options & Accessories

- Standard support stands and guiding options are available
- Available with all standard 2200 & 3200 Series mounting packages and gearmotors



Multiple Spacing Options



Up to (4) conveyors can be coupled together and driven from a single gearmotor.

DORNER MFG. CORP.
PO Box 20 • 975 Cottonwood Ave.
Hartland, WI 53029 USA

INSIDE THE USA
TEL: 800.397.8664
FAX: 800.369.2440

OUTSIDE THE USA
TEL: 262.367.7600
FAX: 262.367.5827

www.dornerconveyors.com
info@dorner.com

