



ELECTRA™

Electric Transporters



ELECTRA™ Electric Transporters

ET-10

ET-20

ET-40



Max Distributed Load (In highest feeding speed)	22 lbs. (10 kg)	44 lbs. (20 kg)	88 lbs. (40 kg)
Max Attached Load (In highest feeding speed)	8.8 lbs. (4 kg)	17.5 lbs. (8 kg)	35 lbs. (16 kg)
Stroke	0.78 in. (20 mm)	0.78 in. (20 mm)	0.78 in. (20 mm)
Feeding Speed (Mechanical adjustable)	13 - 26 Ft/min. (4-8 m/min)	13 - 26 Ft/min. (4-8 m/min)	13 - 26 Ft/min. (4-8 m/min)
Built-in Warning System (Motion sensor)	M12 connector	M12 connector	M12 connector
Start/Stop	M12 connector	M12 connector	M12 connector
Motor and Overload Protection	Built-in	Built-in	Built-in
Noise Level	60 dB(A)	60 dB(A)	60 dB(A)
Energy Consumption	0.05 kW	0.07 kW	0.15 kW
Electricity	110 - 230 VAC, 50 - 60 Hz or 24 VDC	110 - 230 VAC, 50 - 60 Hz or 24 VDC	110 - 230 VAC, 50 - 60 Hz or 24 VDC
Protection Class	IP62	IP62	IP62
Dimensions, (LxWxH)	10.7x4.6x1.5 in. 271x118x38 mm	12.0x5.0x1.9 in. 305x128x47 mm	12.5x5.4x2.7 in. 318x138x68 mm
Weight	5.8 lbs. (2.65 kg)	8.1 lbs. (3.7 kg)	13.9 lbs. (6.3 kg)



WWW.PA.COM

P/A Industries Inc.

522 Cottage Grove Road ▪ Bloomfield, CT 06002-3191 USA
Phone: +1.860.243.8306 ▪ Fax: +1.860.242.4870 ▪ E-Mail: sales@pa.com